FLEXADUX® P4 NEO II

Light weight, two-ply spiral hose made of neoprene®



Applications	extraction systems, vehicle construction, steam extraction, granule drying, automation technology & robotics
Structure	Neoprene® coated glass fabric, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / not coated / copper plated
Temperature	-50°C up to 135°C, short term up to 150°C
Properties	light weight, excellent flexibility, very good temperature resistance, , good chemical resistance





Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
51	54,74	51	2,40	0,53	1,14	4	101101050004
60	63,74	60	2,20	0,53	1,36	4	101101060004
76	79,74	76	2,10	0,44	1,88	4	101101076004
80	83,74	80	2,10	0,40	1,96	4	101101080004
114	118,20	114	1,70	0,30	3,14	4	101101114004

Ocono Romania SRL | Bd. Valea Belciugatele nr. 15 | Comuna Belciugatele | Călărași, 917010 | Romania | T +40 374 20076-5/6 | romania@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026