Ocono

Romania

FURTUN AER COMPRIMAT 20 bar

PVC compressed air hose with polyester fabric reinforcement for compressed air networks and industrial applications

Applications	compressed air, pneumatics, compressors, automation technology & robotics, CNC processing
Structure	soft PVC PVC coated polyester fabric, black, opaque, cross braid
Temperature	-20°C up to 60°C
Properties	high pressure resistance, good flexibility, good abrasion resistance, good low-temperature flexibility, good tensile strength
Norms	Tolerances in accordance with DIN 16940
Optional	different diameters and different lengths available by request



very smooth inside

air

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
6	11,00	2,50	20,00	60,00	6,00	50	110814006050
8	13,00	2,50	20,00	60,00	7,50	50	110814008050
10	15,00	2,50	20,00	60,00	10,00	50	110814010050
12	17,00	2,50	20,00	60,00	11,00	50	110814012050
13	18,00	3,00	20,00	60,00	15,00	50	110814013050
19	26,00	3,50	20,00	60,00	20,50	50	110814019050
25	32,00	3,50	20,00	60,00	29,50	50	110814025050

Ocono Romania SRL | Bd. Valea Belciugatele nr. 15 | Comuna Belciugatele | Călărași, 917010 | Romania | T +40 374 20076-5/6 | romania@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 23.11.2026