

FLEXADUX P4 SIL II

Light weight, two-ply spiral tube made of silicone

- Applications** extraction systems, vehicle construction, steam extraction, granule drying, automation technology & robotics
- Structure** silicone coated glass fabric, brown / red brown (similar RAL 8012), opaque, steel wire / spring steel wire / not coated / copper plated
- Temperature** -70°C up to 250°C, short term up to 300°C
- Properties** light weight, excellent flexibility, very good temperature resistance, , good chemical resistance



Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
25	28,20	25	2,80	0,65	0,88	4	101102025004
38	41,20	38	2,60	0,60	1,20	4	101102038004
41	44,20	41	2,40	0,58	1,28	4	101102041004
44	47,20	44	2,40	0,58	1,34	4	101102044004
51	54,74	51	2,40	0,53	1,40	4	101102051004
55	58,74	55	2,30	0,53	1,64	4	101102055004
60	63,74	60	2,20	0,53	1,84	4	101102060004
63	66,74	63	2,20	0,48	1,92	4	101102063004
76	79,74	76	2,20	0,43	2,28	4	101102076004
80	83,74	80	2,10	0,40	2,44	4	101102080004
83	86,74	83	2,10	0,40	2,52	4	101102083004
102	106,20	102	1,90	0,35	3,56	4	101112102004
127	131,70	127	1,40	0,25	4,00	4	101102127004
152	157,20	152	1,20	0,15	4,80	4	101102152004