

# APDATEC 120

Flexible spiral hose made of PVC with PU inner layer and copper wire for grounding

|                     |                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applications</b> | pellet transport, granulate conveying, extraction systems, conveying of abrasive media, powder conveying & -coating                    |
| <b>Structure</b>    | soft PVC, uncolored, transparent, plastic spiral / rigid PVC, coated strand / copper strand                                            |
| <b>Temperature</b>  | -5°C up to 60°C                                                                                                                        |
| <b>Properties</b>   | good flexibility, very smooth inside, corrugated outside, very good chemical resistance, weather proof, with copper wire for grounding |



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|-------------------|---------------|-----------------------------|------------|----------------|
| 60                  | 68,40               | 4,20                | 270                 | 6,00                          | 0,69              | 1,10000       | 33,00                       | 30         | 112120060030   |
| 75                  | 84,60               | 4,80                | 338                 | 4,00                          | 0,69              | 1,30000       | 39,00                       | 30         | 112120075030   |