FURTUN CAUCIUC EPDM absorbtie si refulare 10 bar

EPDM suction and pressure hose with polyester fabric reinforcement and galvanised steel wire spiral, for water supply, irrigation and construction applications



Applications	irrigation, pump technology, water drain, construction machines, cleaning
Structure	EPDM, black, opaque, steel wire / iron wire / not coated / galvanized
Temperature	-40°C up to 125°C
Properties	high vacuum resistance, high pressure resistance, good abrasion resistance, good ozone- & UV-resistance, very good temperature resistance, smooth inside
Optional	different diameters and different lengths available by request





Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
51	61,00	5,00	204	10,00	30,00	0,93	49,60	40	112555051040
76	88,00	6,00	304	10,00	30,00	0,93	85,60	40	112555076040
90	104,00	7,00	370	10,00	30,00	0,93	110,00	40	112555090040
102	116,00	7,00	405	10,00	30,00	0,93	120,40	40	112555100040
127	141,00	7,00	650	10,00	30,00	0,93	164,00	40	112555127040
152	166,00	7,00	750	10,00	30,00	0,93	238,40	40	112555152040
203	223,00	10,00	1.000	10,00	30,00	0,93	458,40	20	112555203020

Ocono Romania SRL | Bd. Valea Belciugatele nr. 15 | Comuna Belciugatele | Călărași, 917010 | Romania | T +40 374 20076-5/6 | romania@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026