

FURTUN CAUCIUC AER APA 20 bar

Pressure hose with an NR/SBR inner liner, EPDM outer layer and high-strength textile reinforcement for compressed air, water and industrial applications

Applications	compressed air, pneumatics, compressors, agriculture, cleaning
Structure	EPDM, black, opaque
Temperature	-30°C up to 80°C
Properties	high pressure resistance, good resistance to compressed air containing mineral oil, weather proof, good temperature resistance, good tensile strength
Norms	ISO 2398
Optional	different diameters and different lengths available by request



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
6	13,00	3,50	20,00	60,00	7,00	50	110815006013
8	15,00	3,50	20,00	60,00	9,50	50	110815008015
10	18,00	4,00	20,00	60,00	11,50	50	110815010018
13	21,00	4,00	20,00	60,00	16,00	50	110815013021
16	25,00	4,50	20,00	60,00	21,50	50	110815016025
19	29,00	5,00	20,00	60,00	28,50	50	110815019029
25	36,00	5,50	20,00	60,00	37,00	50	110815025036