PROSLIDE PU AS

Very heavy weight spiral hose made of PVC with highly abrasion resistant PU inner layer and copper wire for grounding



Applications	roof graveling, conveying of rubble, gravel conveying, sandblasting, conveying of abrasive media
Structure	soft PVC, yellow, opaque, plastic spiral / rigid PVC, coated strand / copper strand
Temperature	-20°C up to 60°C
Properties	very good abrasion resistance, high vacuum resistance, crush-resistant, very smooth inside, corrugated outside, with highly abrasion-resistant polyurethane inner layer, smooth, to ensure very low pressure losses, good mechanical strength





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
51	61,40	5,20	345	6,00	0,88	0,90000	30,36	30	112500051030

Ocono Romania SRL | Bd. Valea Belciugatele nr. 15 | Comuna Belciugatele | Călărași, 917010 | Romania | T +40 374 20076-5/6 | romania@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026