

FURTUN CAUCIUC EPDM

absorbție și refulare 10 bar

EPDM suction and pressure hose with polyester fabric reinforcement and galvanised steel wire spiral, for water supply, irrigation and construction applications

Applications	irrigation, pump technology, water drain, construction machines, cleaning
Structure	EPDM, black, opaque, steel wire / iron wire / not coated / galvanized
Temperature	-40°C up to 125°C
Properties	high vacuum resistance, high pressure resistance, good abrasion resistance, good ozone- & UV-resistance, very good temperature resistance, smooth inside
Optional	different diameters and different lengths available by request



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
51	61,00	5,00	204	10,00	30,00	0,93	49,60	40	112555051040
76	88,00	6,00	304	10,00	30,00	0,93	85,60	40	112555076040
90	104,00	7,00	370	10,00	30,00	0,93	110,00	40	112555090040
102	116,00	7,00	405	10,00	30,00	0,93	120,40	40	112555100040
127	141,00	7,00	650	10,00	30,00	0,93	164,00	40	112555127040
152	166,00	7,00	750	10,00	30,00	0,93	238,40	40	112555152040
203	223,00	10,00	1.000	10,00	30,00	0,93	458,40	20	112555203020