

FURTUN ASPIRATIE INOVASTEEL

Flexible hose made of soft PVC

- Applications** granulate conveying, dosing, food production & -conveying, agricultural technology, irrigation
- Structure** PVC, uncolored, transparent, steel wire / iron wire / not coated / galvanized
- Temperature** -20°C up to 65°C
- Properties** good flexibility, crush-resistant, very high vacuum resistance, smooth outside, smooth inside, phthalate-free
- Norms** A, B, C | certified according to Food EU Directive (EC) No. 1935/2004 & Regulation (EC) No. 10/2011 for A, B, C



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
19	26,00	3,50	57	11,00	0,88	0,33000	9,90	30	117009019030
19	26,00	3,50	57	11,00	0,88	0,33000	16,50	50	117009019050
20	27,00	3,50	60	10,00	0,88	0,38000	17,00	50	117009020050
25	33,00	4,00	75	10,00	0,88	0,52000	26,00	50	117009025050
32	40,40	4,10	96	9,00	0,88	0,66000	19,80	30	117009032030
32	40,40	4,10	96	9,00	0,88	0,66000	33,00	50	117009032050
35	43,60	4,30	105	9,00	0,88	0,72600	37,50	50	117009035050
38	47,00	4,20	114	9,00	0,88	0,89600	39,00	50	117009038050
40	49,60	4,80	120	9,00	0,88	0,95000	46,50	50	117009040050
45	55,00	4,90	135	9,00	0,88	1,15000	57,50	50	117009045050
51	61,80	5,40	150	7,00	0,88	1,30000	39,00	30	117009051030
51	61,80	5,40	150	7,00	0,88	1,30000	65,00	50	117009051050
75	88,40	6,70	225	5,00	0,88	2,18000	65,40	30	117009075030