

FURTUN PRESIUNE SEMPERIT PLW 20 bar

Pressure hose with an oil-mist-resistant synthetic rubber inner liner, textile reinforcement and a weather-resistant outer layer for compressed air, water and construction site applications

Applications	compressed air, pneumatics, compressors, cleaning, water cooling
Structure	black, opaque
Temperature	-30°C up to 70°C
Properties	high pressure resistance, good resistance to compressed air containing mineral oil, good ozone- & UV-resistance, weather proof, good tensile strength, smooth inside, smooth outside
Norms	ISO 1307
Optional	different diameters and different lengths available by request



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
6	12,00	3,00	20,00	60,00	8,50	50	700084006050
8	15,00	3,50	20,00	60,00	8,50	50	700084008050
10	17,00	3,50	20,00	60,00	10,00	50	700084010050
13	21,00	4,00	20,00	60,00	12,00	50	700084013050
16	23,00	3,50	20,00	60,00	14,50	50	700084016050
19	26,00	3,50	20,00	60,00	17,50	50	700084019050
25	33,00	4,00	20,00	60,00	24,50	50	700084025050
32	45,00	6,50	20,00	60,00	55,00	50	700084032050
38	51,00	6,50	20,00	60,00	60,00	50	700084038050