
ONEFLAT SL

Lightweight PVC flat hose with polyester fabric reinforcement for water conveyance, hydraulic protection and drainage applications in the construction industry

Applications	pump technology, water drain, irrigation, construction machines, agriculture
Structure	soft PVC PVC coated polyester fabric, blue, opaque
Temperature	-20°C up to 65°C
Properties	good flexibility, good tensile strength, good temperature resistance, high pressure resistance
Optional	different diameters and different lengths available by request



liquids

Inner Diameter (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
127	3,00	10,00	37,50	50	111274127050
127	3,00	10,00	75,00	100	111274127100
152	3,00	10,00	45,00	50	111274152050
152	3,00	10,00	90,00	100	111274152100
203	2,00	8,00	80,00	50	111274203050

Ocono Romania SRL | Bd. Valea Belciugatele nr. 15 | Comuna Belciugatele | Călărași, 917010 | Romania | T +40 374 20076-5/6 | romania@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026