FURTUN INOVAFLAT

Flexible PVC flat hose with polyester fabric reinforcement for irrigation, pumping systems and construction applications

Applications	irrigation, agriculture, pump technology, construction machines, water drain
Structure	soft PVC PVC coated polyester fabric, blue, opaque, cross braid
Temperature	-10°C up to 60°C
Properties	high pressure resistance, good abrasion resistance, good flexibility, good low-temperature flexibility, good chemical resistance
Norms	Tolerances in accordance with DIN 16940
Optional	different diameters and different lengths available by request







Inner Diameter (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
25	7,00	21,00	8,50	50	111252025050
32	6,00	18,00	11,00	50	111252032050
38	6,00	18,00	12,50	50	111252038050
50	4,00	12,00	14,00	50	111252050050
63	3,00	10,00	18,00	50	111252063050
75	3,00	10,00	21,00	50	111252075050
100	3,00	9,00	30,00	50	111252100050

Ocono Romania SRL | Bd. Valea Belciugatele nr. 15 | Comuna Belciugatele | Călărași, 917010 | Romania | T +40 374 20076-5/6 | romania@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 23.11.2026