ONEFLAT GERMANY HD

Heavy-Duty PVC-Flachschlauch mit Polyester-Gewebeverstärkung für Bau, Pumpentechnik und Hochdruck-Wasserförderung

Applications	pump technology, irrigation, fire damage restoration, water drain, construction machines
Structure	PVC coated polyester fabric, white, opaque, cross braid
Temperature	-10°C up to 60°C
Properties	very high pressure resistance, very good abrasion resistance, very good low-temperature flexibility, good flexibility, good ozone- & UV-resistance, weather proof
Optional	different diameters and different lengths available by request







Inner Diameter (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
100	14,00	40,00	55,00	100	111302100100
125	14,00	40,00	73,80	100	111302125100
150	14,00	40,00	100,50	100	111302150100

Ocono Romania SRL | Bd. Valea Belciugatele nr. 15 | Comuna Belciugatele | Călărași, 917010 | Romania | T +40 374 20076-5/6 | romania@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026